

# SPECIFICATIONS



## Ducted Split System -

Model Number	WGS40	WGS75	WGS100 (50Hz)
<b>Performance</b>			
Net Cooling * Total Sensible	Total/Sensible @220-2400V	Total/Sensible @220-240V	Total/Sensible @220-240V
@10°F (minus 12°C) condenser inlet air	1140/879 Watts	1600/1300 Watts	2960/2315 Watts
@40°F (4°C) condenser inlet air	1140/937 Watts	1780/1460 Watts	2930/2285 Watts
@60°F (15°C) condenser inlet air	1115/860 Watts	1715/1440 Watts	3077/2256 Watts
@70°F (21°C) condenser inlet air	1110/850 Watts	1750/1380 Watts	2930/2168 Watts
@80°F (27°C) condenser inlet air	1055/835 Watts	1550/1310 Watts	2813/2110 Watts
@100°F (32°C) condenser inlet air	965/730 Watts	1360/1150 Watts	2520/1846 Watts
@115°F (46°C) condenser inlet air	850/675 Watts	1300/1080 Watts	2373/1758 Watts
@122°F (50°C) condenser inlet air	640/640 Watts	1200/1000 Watts	
<b>Controls</b>			
Type	Room mounted non-programmable combination thermostat humidistat		
Temperature Accuracy/RH% Accuracy	+/- 1 Deg F / +/- 10% RH		
<b>Fan-coil Section</b>			
Fan Motor Size	85 Rated Watts	120 Rated Watts	230 Rated Watts
Rated Air Flow (free blow)	390 M <sup>3</sup> h	680 M <sup>3</sup> h	N/A
Rated Air Flow @ Max allow pressure loss	374 M <sup>3</sup> h	630 M <sup>3</sup> h	750 M <sup>3</sup> h
<b>Heat (Option)</b>			
Type	Electric	Electric	Electric
Capacity	1000 Watts	1000 Watts	2000 Watts
<b>Humidifier (Option)</b>			
Type	Removeable drip pad with integral fan		
Capacity - water temp of 60°F (15°C)	.19 kg/hr	.19 kg/hr	.19 kg/hr
Capacity - water temp of 90°F (32°C)	.44 kg/hr	.44 kg/hr	.44 kg/hr
Capacity - water temp of 120°F (49°C)	0.5 kg/hr	0.5 kg/hr	0.5 kg/hr
<b>Electrical Requirements - Evaporator Section</b>			
Power	220-240Volts/1 phase/50Hz	220-240Volts/1 phase/50Hz	220-240Volts/1 phase/50Hz
Current Draw - Cooling mode	0.4 Amps	0.5 Amps	1.0 Amps
Current Draw - Heating mode	4.75 Amps	4.70 Amps	10.7 Amps
Minimum Circuit Size (w/heat option)	5.84 Amps	5.75 Amps	13.1 Amps
Optional Humidifier	0.3 Amps	0.3 Amps	0.3 Amps
<b>Cabinet - Evaporator Section</b>			
Fan coil construction	Aluminum		
Finish	Black - textured epoxy powder coat		
Weight	11.3 kg	15.5 kg	15.5 kg
Length	42.5 cm	42.5 cm	42.5 cm
Width	35.6 cm	55.8 cm	55.8 cm
Height	35.8 cm	35.6 cm	35.8 cm
Condensate Drain	12.7 mm	12.7 mm	12.9 mm
<b>Condensing Unit</b>			
	<b>WGS40 Cond</b>	<b>WGS75 Cond</b>	<b>WGS100 Cond</b>
Nominal Compressor	2.6 Amps	3.9 Amps	10.8 Amps
Fan Motor Size	68 Watts	68 Watts	120 Watts
Rated Air Flow (free blow)	850 M <sup>3</sup> h	850 M <sup>3</sup> h	739 M <sup>3</sup> h
Weight	34 kg	35 kg	69 kg
<b>Enclosure - Condensing Unit</b>			
Construction	Aluminum	Aluminum	Aluminum
Finish	Powder-coated	Powder-coated	Powder-coated
Width	22.86 cm	31.17 cm	31.24 cm
Length	86.36 cm	86.36 cm	86.36 cm
Height	63.80 cm	66.04 cm	68.73 cm
<b>Electrical Requirements - Condensing Unit</b>			
Power	220-240 Volts/1 Phase/50Hz	220-240 Volts/1 Phase/50Hz	220-240 Volts/1 Phase/50Hz
MCA	3.7 Amps	5.2 Amps	14.2 Amps
MOP	6.0 Amps	9.0 Amps	20 amps
<b>Agency Approval(s)</b>			
	CE	CE	CE

1. Net cooling capacity at entering temperature and humidity conditions of 57 Deg F (14 Deg C) and 55% RH at rated airflow. Reduce capacity by 3% for each 10% reduction in evaporator airflow.

2. Wine Guardian reserves the right to make changes to this document without prior notice at its sole discretion.

3. All ratings at sea level.